

## **Supplier's Declaration of Conformity for Material Declaration Management**

- 1) SDoC No.: 365193-10023
- 2) Issuer's name: Engine Protection Partner AS
- Issuer's address: O. J. Brochs gate 16A. 5006 Bergen
- 3) Object(s) of declaration: 1)Flexible Bellow
- 2)
- 3)
- 4)

- 4) The object(s) of the declaration described above is/are in conformity with the following documents:

- 5) Applicable Regulations or other stipulated requirements and documents

Document No.	Title	Edition	Date of issue

- 6) Additional Information: Oil mist detector spare part

Signed for and on behalf of: Engine Protection Partner AS/ Lise Frøysa

Bergen/ Norway

Place of issue

05.01.2121

Date of issue

- 7) Lise Frøysa - QM

Name, function

Signature

**Engine Protection Partner AS**  
Schaller Automation Scandinavia & Baltics  
O. J. Brochs gate 16A, 2nd floor, 5006 Bergen, Norway  
Org. nr.: 976 683 560 | Phone: +47 5530 1900  
E-mail: info@epp.no | Website: www.epp.no

# Material Declaration

## <Date of declaration>

Date	05.01.2021
------	------------

## <MD ID number>

MD-ID-No.	365193-10023
-----------	--------------

## <Supplier (respondent) information>

Company name	Engine Protection Partner AS
Division name	Head Office Bergen
Address	O. J. Brochs gate 16A. 5006 Bergen
Contact person	Yngve Nilsen/ Lise Frøysa
Telephone number	+47 55301900
Fax number	+47 55301901
E-mail address	epp@epp.no
SDoC ID-No.	365193-10023

## <Other information>

Remark 1	
Remark 2	
Remark 3	

## <Product information>

Product name	Product number	Delivered unit		Product information
		Amount	Unit	
Flexible Bellow	365193-10023	1	piece	Oil mist detector spare part

## <Material information>

This materials information shows the amount of hazardous materials contained in	Unit
	1 piece

Table	Material name		Threshold level	Present above threshold level	If yes, material mass		If yes, information on where it is used
				Yes/No	Mass	Unit	
Table A** (materials listed in appendix 1 of the Convention)	Asbestos		0.1%*	No			
	Polychlorinated biphenyls (PCBs)		50 mg/kg	No			
	Ozon depleting substance	Chlorofluorocarbons (CFCs)	no threshold level	No			
		Halons		No			
		Other fully halogenated CFCs		No			
		Carbon tetrachloride		No			
		1,1,1-Trichloroethane		No			
		Hydrochlorofluorocarbons		No			
		Hydrobromofluorocarbons		No			
		Methyl bromide		No			
		Bromochloromethane		No			
	Anti-fouling systems containing organotin compounds as a biocide		2,500 mg total tin/kg	No			
Table B** (materials listed in appendix 2 of the Convention)	Cadmium and cadmium compounds		100 mg/kg	No			
	Hexavalent chromium and hexavalent chromium compounds		1,000 mg/kg	No			
	Lead and lead compounds		1,000 mg/kg	No			
	Mercury and mercury compounds		1,000 mg/kg	No			
	Polybrominated biphenyl (PBBs)		50 mg/kg	No			
	Polybrominated diphenyl ethers (PBDEs)		1,000 mg/kg	No			
	Polychloronaphthalenes (Cl >= 3)		50 mg/kg	No			
	Radioactive substances		no threshold level	No			
	Certain shortchain chlorinated paraffins		1%	No			
Annex II*** (Additional materials)	Perfluorooctane sulfonic acid (PFOS)		10 mg/kg****	No			
	Brominated Flame Retardant (HBCDD)		100 mg/kg	No			

\*Please refer to footnote 18 on the "Form of Material Declaration" in the IMO Guidelines Resolution MEPC.269(68).

\*\*Hong Kong International Convention for the Safe and Environmentally Sound Recycling of Ships, 2009 (SR/CONF/45).

\*\*\*Regulation EU No. 1257/2013 of the European Parliament and of the Council of 20 November 2013 on Ship Recycling and amending Regulation EC No. 1013/2006 and Directive 2009/16/EC

\*\*\*\*EMSA's Best Practice Guidance on the Inventory of Hazardous Materials, dated 2016-10-28

\*\*\*\*\*Concentrations of PFOS above 10 mg/kg (0.001% by weight) when it occurs in substances or in preparations or concentrations of PFOS in semi-finished products or articles, or parts thereof equal to or above than 0.1% by weight calculated with reference to the mass of structurally or micro-structurally distinct parts that contain PFOS or for textiles or other coated materials, if the amount of PFOS is equal to or above than 1 µg/m² of the coated material.